



TIMKEN E-PF-TRB-4 15/16 Flange Block Bearings

Bearing No. E-PF-TRB-4 15/16

E-PF-TRB-4 15/16 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	59.02
EAN	0053893778792
Product Group	M06288
Number of Mounting Holes	6
Mounting Method	Concentric Collar
Housing Style	6 Bolt Round Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	7/8 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Inch
Long Description	6 Bolt Round Flange Block; 4-15/16" Bore; 12.8" Bolt Circle; 6-3/8" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Tapered Roller Bearing; 7-1/4" Length Thru Bore
Other Features	Double Row Wide Inner Race With Set Screw



handong Zhiyuan Bearing Co., Ltd

Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	E-PF-TRB-4 15/16
Weight / LBS	130
Nominal Bolt Circle Diameter Round	12.8 Inch 325.1 Millimeter
Cartridge Pilot Diameter	11 Inch 279.4 Millimeter
Cartridge Pilot Depth	3.188 Inch 80.975 Millimeter
d	4.938 Inch 125.425 Millimeter
Bolt Spacing	6.375 Inch 161.925 Millimeter
D	7.25 Inch 184.15 Millimeter
Shaft Size	4.9375 in
Shaft Size Type	Imperial
Weight	130.000 lb
UPC Code	053893778792
Dimension B	7-1/4 in
Dimension H	14-3/4 in
Dimension A	5-1/16 in
Dimension N ₂	6.375 in
Dimension J	12-3/4 in
Dimension A ₃	1-3/4 in
Bolt Diameter	7/8 in
Dimension E	2-31/32 in
Dimension A ₁	1-1/4 in
Dimension D ¹	11 in
Dimension d ₁	7-3/4 in



handong Zhiyuan Bearing Co., Ltd

Dimension A_2	1-7/8 in
e	0.47
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	1.83
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.21
K Factor	1.27
C_{90} Dynamic Load Rating ²	45500 lb
C_0 Static Load Rating	266000 lb
F_{a-max} Maximum Permissible Thrust Load ³	6908 lb
F_{r-max} Maximum Allowable Slip Fit Radial Load ⁴	35000 lb
Max. Speed ⁵	1200 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur